

FIBER OPTIC TERMINAL BOX

FC-44-OTB-I4A | FC-44-OTB-I4B

Series Overview

The FiberCore FC-44-OTB-I4 Series features compact indoor fiber optic terminal boxes designed for reliable end-point terminations. Ideal for wall-mounted use in residential settings, they offer secure, flexible solutions for fiber fixing, splicing, and pigtail management.

Applications

- FTTH
- Optical communication system

Product Introduction



OTB 4 PORT STANDARD INDOOR LOADED

Models: FC-44-OTB-I4A

Product Overview

The FiberCore FC-44-OTB-I4A is an indoor fiber optic terminal box designed for end-point terminations in residential buildings and villas. Engineered for wall-mounted installation, it supports various optical connection styles and provides a secure interface for fixing and splicing fibers with pigtails.

Features

- Max capacity: 4 cores
- Can load 4 Mechanical splices for drop cables
- Input Port Suitable Cable diameter 7-10mm
- Indoor wall mount application
- Cable entry without cutting

Accessories

- Heat Protection Sleeves
- Integrated Splice Tray
- Dust cap for adapters
- Installation kit (tox, screws, mini cable ties)

Dimension	Material	Color	Adapter Port	Splicing Capacity	Cable port	Mounting
150x110x34mm	ABS Plastic	White	4 Ports (SC simplex / LC duplex)	4 to 8 fibers	2 cable ports	Wall-mounted



Want to know more about FiberCore?

For more information visit www.fibercore-plus.com or contact sales@fibercore-plus.com

V1.0 - 09012025

FIBER OPTIC TERMINAL BOX

FC-44-OTB-I4A | FC-44-OTB-I4B

Product Introduction



OTB 4 PORT SHUTTERED INDOOR LOADED

Models: FC-44-OTB-I4B

Product Overview

The FiberCore FC-44-OTB-I4B is an indoor fiber optic terminal box designed for end-point terminations in residential buildings and villas. Engineered for wall-mounted installation, it supports various optical connection styles and provides a secure interface for fixing and splicing fibers with pigtailed.

Features

- Max capacity: 4 cores
- Can load 4 Mechanical splices for drop cables
- Input Port Suitable Cable diameter 7-10mm
- Indoor wall mount application
- Cable entry without cutting

Accessories

- Heat Protection Sleeves
- Integrated Splice Tray
- Dust cap for adapters
- Installation kit (tox, screws, mini cable ties)

Dimension	Material	Color	Adapter Port	Splicing Capacity	Cable port	Mounting
130x180x30mm	ABS Plastic	White	4 Ports (SC simplex / LC duplex)	4 to 8 fibers	3 to 4 cable ports	Wall-mounted

Ordering Information

Description	Part No.
OTB 4 Port Standard Indoor Loaded	FC-44-OTB-I4A
OTB 4 Port Shuttered Indoor Loaded	FC-44-OTB-I4B



Want to know more about FiberCore?

For more information visit www.fibercore-plus.com or contact sales@fibercore-plus.com

V1.0 - 09012025